

PTZ Speed Domes

JCC-DN4636WD

Indoor Day/Night Speed PTZ Dome

JCC-DN4736WD

Outdoor Day/Night Speed PTZ Dome



Indoor PTZ Speed Dome



Outdoor PTZ Speed Dome

Features

- ↘ Multi-protocol Decoder Built-in
- ↘ 1/4" Sony Ex-View HAD CCD Sensor
- ↘ 535 TV Lines
- ↘ 36X Optical Zoom
- ↘ 12X Digital Zoom
- ↘ IP 66 Waterproof Standard (JCC-DN4736WD only)
- ↘ Wide Dynamic Range
- ↘ OSD Operation
- ↘ Auto IR Cut Filter Removal
- ↘ 128 Preset Points
- ↘ RS-485 Communication Port
- ↘ Private Zone Masking
- ↘ AC 24±4V

Model	JCC-DN4636WD	JCC-DN4736WD
Image Sensor	1/4" Day & Night Sony Ex-View HAD CCD	
Camera Type	Sony EX-1010	
Horizontal Resolution	Horizontal 535 TV Lines	
Synchrone System	Internal/External	
Auto ICR	YES (IR Cut Filter Removal)	
Privacy Zone Masking	YES	
Digital Zoom Ratio	YES	
Electrical		
Power Supply	AC 24±4V	
Power Consumption	10W	50W
Operational		
Receiver	Built-in	
Motor	Stepping motor	
Preset position	128 presets, can be labeled with editable title	
Alarm function	4 alarm input/2 alarm output, alarm linkage available.	
Pan rotation range	Continuously 360°	
Manual pan speed	0.4° - 320°/S	
Auto pan scan	355° programmable	
Tilt rotation range	tilt 90°, with auto flip	
Manual vertical speed	0.4° - 320°/S	
Preset time	< 1 s	
Communication	Peleco-D 2400 / Peleco-P 4800 / 9600 / AD / Samsung / Philips / Vcion ect.	
Baud rate (RS485)	2400/4800/9600/19200bps	
Environmental		
Operating temperature	0° ~ +50°	-40° ~ +60°
Environmental humidity	0 ~ 95% (no condensation)	
Protection grade	-----	IP66, TVS 1500w lightning proof & surge proof
Physical		
Dimension (mm)	300× 215mm	300× 231mm
N.W. / G.W.	5.36kg / 7.75Kg	4.45Kg / 6.84Kg

Dimension

