


**Features:**

- \* 1/3" Sony 2.4 MP CMOS Sensor (IMX323)
- \* AHD/TVI/CVI 1080P Video & CVBS
- \* Multi-Language OSD Setup Menu
- \* Programmable ES & Auto White Balance
- \*
- \* 3.6mm Megapixel Lens
- \* UTC Function
- \* Plastic Construction
- \* DC 12V Power
- \*

Model	SSV-XHD-808S32
Pick-Up Element	1/3" SONY 2.4 Megapixel Progressive Scan Exmor CMOS Sensor (IMX323)
Picture Element	1984(H) × 1105(V)
Video Standard	NTSC / PAL
Resolution	1920 x 1080 (1080P) @ 25/30 fps
Optical Filter	With IR-Cut Filter Removable (ICR) Design
Synchronization	Internal
Scanning System	Progressive Scan
Min. Illumination	0.05 Lux /F2.0 (50 IRE) ; 0Lux IR-LEDs ON
S/N Ratio	More Than 56dB (AGC OFF)
WDR Range	Smart WDR Open / Close
OSD Menu	Multi-Languages OSD Menu with UTC Function
Day/Night Mode	External / Color / B&W / Internal
AE Mode	Normal / Front Light / Back Light
Electronic Shutter	Auto: 1/30, 1/60, 1/120, 1/240, 1/500, 1/2000, 1/5000,1/10000, 1/100000
White Balance	Auto / Gray World
Brightness	256 – 1024 Level Adjustable
Saturation	0 – 504 Level Adjustable
Transmission Distance	Over 300-500 Meter on RG59/RG6U Coaxial Cable, 300 Meter on Twisted Cable
UTC Function	Support (OSD Menu Can be Accessed on TVI DVRs with UTC Function)
Water-proof	N/A
Video Output	AHD/TVI/CVI Video & Analog Composite Video Switchable
Lens	3.6mm Lens (Optional with 4.0mm, 6.0mm or 8.0mm Lens)
Operating Temperature	-10 - +50 degree / RH 85% or Less
Power	DC 12V ± 10%
Dimension	87mm (Dia.) x 53mm
Weight	170 Gram
Construction	Plastic

\* Specifications subject to be changed without notice